Journal of Emerging Intelligence and Engineering Technologies

Research Article

Cloud-Driven Threat Reconstruction Using Generative AI and Semantic Intelligence Across Distributed Enterprise Networks

D.Durga Prasad

Professor, Dept of CSE, PSCMR College of Engg., & Tech, Vijayawada, India

Abstract

The increasing complexity of distributed enterprise networks has created significant challenges in identifying, investigating, and reconstructing sophisticated cybersecurity threats. Traditional security investigation techniques frequently depend on isolated security logs, predefined detection rules, and manual correlation processes, limiting their ability to identify complex attack sequences across hybrid and multi-cloud environments. This research proposes a cloud-driven threat reconstruction framework integrating Generative Artificial Intelligence (GenAI), semantic intelligence, and distributed security analytics to improve enterprise threat investigation. The proposed framework collects heterogeneous security information from cloud infrastructure, network devices, applications, identity management systems, and endpoint protection platforms. Semantic intelligence transforms collected security events into contextual relationships, enabling the identification of attack patterns, suspicious activities, and relationships between interconnected infrastructure components. Generative AI enhances investigation by correlating security evidence, reconstructing potential attack sequences, generating contextual incident explanations, and supporting automated threat intelligence analysis. A knowledge graph-based representation enables relationships among attackers, vulnerabilities, affected resources, and attack techniques to be examined systematically. The framework additionally incorporates explainable AI, continuous monitoring, and evidence validation to improve investigation transparency and reliability. The proposed approach aims to strengthen enterprise cyber resilience through faster incident reconstruction, improved threat visibility, and intelligent security decision-making across distributed cloud environments.

Keywords: Generative Artificial Intelligence, Cloud Security, Threat Reconstruction, Semantic Intelligence, Distributed Enterprise Networks, Cyber Threat Intelligence, Knowledge Graphs, Security Analytics, Incident Investigation, Explainable AI

Received: 22 July 2025
Revised: 10 August 2025
Accepted: 28 August 2025
Published: 30 october2025

© 2025 The Author(s). Published by the Journal of Emerging Intelligence and Engineering Technologies. This is an open-access article distributed under the terms of the Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0), which permits use, distribution, and reproduction in any medium for non-commercial purposes, provided the original work is properly cited. https://creativecommons.org/licenses/by-nc/4.0/ Deed - Attribution-NonCommercial 4.0 International - Creative Commons

Introduction

The rapid adoption of cloud computing, distributed applications, hybrid infrastructure, and interconnected enterprise networks has fundamentally transformed organizational information technology environments. Modern enterprises increasingly depend on geographically distributed cloud resources, containerized applications, microservices, software-defined networks, and third-party application integrations to support business operations. Although these technologies improve scalability, flexibility, and operational efficiency, they also introduce complex cybersecurity challenges. Security incidents can originate from compromised endpoints, unauthorized identity access, malicious application programming interfaces, vulnerable cloud workloads, and interconnected network services. These incidents frequently propagate across multiple infrastructure

components before security teams recognize their complete impact. Traditional cybersecurity investigation methods generally examine individual security alerts, network logs, authentication records, and application events independently. Consequently, investigators may experience difficulties establishing relationships between seemingly unrelated activities, identifying initial attack vectors, and reconstructing the complete sequence of malicious operations. Distributed enterprise environments require intelligent investigation mechanisms capable of integrating security information from heterogeneous infrastructure sources while maintaining contextual relationships between events. Cloud-driven threat reconstruction provides an opportunity to address these challenges by collecting, processing, correlating, and analyzing security evidence across distributed environments. The integration of Generative Artificial Intelligence introduces additional capabilities for understanding complex security information, summarizing incident evidence, identifying suspicious behavioral patterns, and generating investigation explanations. Semantic intelligence further improves these capabilities by interpreting relationships between security entities, infrastructure resources, vulnerabilities, identities, and observed attack behaviors. Through these combined technologies, organizations can move beyond isolated alert detection toward comprehensive and context-aware cybersecurity investigation. Such an approach is particularly important for enterprises operating multi-cloud and hybrid environments where security visibility, operational ownership, and incident evidence are distributed across different platforms.

The primary objective of this research is to develop a cloud-driven threat reconstruction framework using Generative AI and semantic intelligence to improve cybersecurity investigation across distributed enterprise networks. The proposed framework combines centralized security data integration, semantic event representation, knowledge graph construction, generative threat analysis, and explainable incident reconstruction. Initially, security information is collected from cloud monitoring platforms, intrusion detection systems, endpoint security solutions, identity providers, firewalls, and application monitoring services. The collected information is normalized and transformed into structured representations to support cross-platform analysis. Semantic intelligence identifies relationships among users, devices, IP addresses, cloud services, attack indicators, and infrastructure dependencies. A knowledge graph subsequently represents these relationships and supports contextual investigation of complex security incidents. Generative AI analyzes correlated evidence to identify potential attack progression, summarize investigation findings, and explain the relationships between individual security events. The framework also incorporates confidence assessment, evidence traceability, and human approval to reduce unsupported conclusions and prevent inappropriate automated responses. The research focuses on improving threat reconstruction accuracy, investigation efficiency, attack visibility, and decision-making capabilities in distributed enterprise environments. It also considers challenges involving heterogeneous data formats, incomplete security records, privacy protection, computational overhead, and the reliability of AI-generated explanations. The intended contribution is an integrated analytical architecture that connects cloud security intelligence with semantic reasoning and generative investigation capabilities. By establishing contextual relationships across distributed security events, the framework seeks to support proactive threat investigation and strengthen organizational cyber resilience.

Literature Review

The development of cloud computing has significantly influenced enterprise cybersecurity monitoring and incident investigation practices. Traditional security information and event management systems provide centralized mechanisms for

collecting and analyzing security logs from different infrastructure components. However, conventional monitoring approaches frequently depend on predefined correlation rules and isolated event analysis, which can limit their effectiveness against sophisticated attacks involving multiple interconnected systems. Research in distributed intrusion detection has demonstrated the importance of correlating network traffic, endpoint activities, authentication events, and application behavior to identify suspicious operational patterns. Cloud-native monitoring platforms and security analytics technologies have further improved visibility across virtual machines, containers, serverless applications, and distributed services. Nevertheless, differences in log formats, event timestamps, security policies, and infrastructure configurations create significant integration challenges. Security investigators must frequently examine large volumes of heterogeneous records to determine whether individual alerts represent independent incidents or components of a coordinated attack. Distributed environments also introduce difficulties in maintaining consistent investigation context when evidence originates from multiple cloud providers and geographically separated infrastructure resources. Existing research on security event correlation highlights the importance of contextual analysis, temporal relationships, and behavioral dependencies for improving incident identification. These developments establish the foundation for intelligent threat reconstruction systems that combine centralized cloud monitoring with distributed security intelligence. However, comprehensive reconstruction requires more than event aggregation because security systems must understand the semantic meaning and relationships associated with collected evidence.

Semantic intelligence and knowledge graph technologies have emerged as important approaches for representing interconnected cybersecurity information. Semantic models enable security events to be interpreted through structured relationships involving users, devices, applications, vulnerabilities, attack techniques, and infrastructure resources. Knowledge graphs provide a flexible representation in which security entities are modeled as nodes and their relationships are represented as edges. This structure enables investigators to identify relationships between compromised accounts, suspicious network connections, affected cloud services, and known attack indicators. Cyber threat intelligence frameworks, including structured representations of adversary tactics and techniques, support the classification and interpretation of observed malicious activities. Standards such as STIX and ATT&CK provide useful foundations for integrating threat intelligence with enterprise security investigation processes. Graph-based approaches can also support attack-path analysis, entity resolution, threat attribution assistance, and investigation prioritization. Despite these advantages, semantic security systems face challenges involving incomplete information, inconsistent entity identification, changing infrastructure relationships, and uncertainty in threat intelligence sources. Knowledge graphs must be continuously updated to represent dynamic cloud environments accurately. Furthermore, relationships identified through automated correlation do not always establish direct causal connections between events. Therefore, reliable threat reconstruction requires temporal analysis, source verification, confidence evaluation, and explicit distinction between observed evidence and inferred relationships. Integrating semantic intelligence with cloud monitoring can improve investigation context, but additional analytical capabilities are necessary to interpret complex attack scenarios and communicate findings effectively to security analysts.

Recent developments in Generative AI and large language models have created new opportunities for cybersecurity investigation and intelligent security operations. Generative models can process unstructured security information, summarize lengthy incident reports, interpret technical descriptions, and

generate contextual explanations from correlated evidence. Their application in security operations can support alert investigation, threat intelligence enrichment, vulnerability interpretation, and incident response documentation. Retrieval-Augmented Generation (RAG) provides an additional mechanism for connecting generative models with trusted organizational knowledge bases, security policies, threat intelligence repositories, and historical incident records. This integration can improve the relevance of generated responses by grounding model outputs in retrieved evidence. Research involving AI-assisted cybersecurity analysis also highlights the potential of combining machine learning with security knowledge graphs to improve contextual threat understanding. However, Generative AI introduces important limitations, including hallucinated explanations, inaccurate threat attribution, sensitivity to incomplete evidence, prompt injection, and inconsistent reasoning. These limitations are particularly important in enterprise incident reconstruction, where unsupported conclusions can lead to incorrect security decisions. Explainable AI, evidence-grounded generation, source attribution, and human oversight are therefore necessary components of reliable AI-driven security investigation. Existing approaches frequently examine generative security assistance, semantic threat representation, and distributed cloud monitoring as separate capabilities. There remains an opportunity to integrate these technologies into a unified architecture that reconstructs attack progression across heterogeneous enterprise infrastructure. The proposed research addresses this opportunity through a combination of cloud-driven evidence collection, semantic knowledge representation, graph-based correlation, and evidence-grounded generative reasoning.

Research Methodology

Research Design and Proposed Framework Architecture

The research adopts a design-oriented and experimental methodology to develop a cloud-driven threat reconstruction framework integrating Generative AI and semantic intelligence across distributed enterprise networks. The proposed architecture is designed to investigate cybersecurity incidents involving interconnected cloud services, enterprise applications, network infrastructure, user identities, and endpoint devices. The methodology follows a layered architecture consisting of security data acquisition, preprocessing and normalization, semantic intelligence processing, knowledge graph construction, generative threat analysis, and explainable investigation output. The data acquisition layer collects security information from heterogeneous sources, including cloud audit logs, firewall records, intrusion detection alerts, endpoint detection systems, identity and access management platforms, application monitoring services, vulnerability scanners, and network traffic analysis tools. These sources provide complementary information about user authentication, resource access, application execution, network communication, configuration changes, and suspicious activities. The collected information is transmitted through secure cloud-based ingestion pipelines using standardized interfaces and event streaming mechanisms. The framework supports integration with public cloud, private cloud, hybrid cloud, and multi-cloud infrastructure environments. Each incoming security record is associated with relevant metadata, including event identifiers, source systems, timestamps, severity classifications, resource identifiers, and collection information. This metadata provides the foundation for maintaining evidence traceability throughout the investigation process. The architecture also incorporates secure communication channels, role-based access control, encryption, and tenant isolation to protect sensitive enterprise security information. A distributed processing mechanism supports the ingestion of high-volume security events

without requiring every infrastructure component to communicate directly with the generative analysis engine. Instead, intermediate processing services perform initial validation and filtering before forwarding relevant information to subsequent analytical components. This modular architecture allows individual components to be upgraded or scaled independently. The research evaluates the proposed architecture through controlled attack scenarios and comparative analysis against conventional security event correlation techniques. The primary methodological emphasis is on establishing a reliable relationship between distributed security evidence and reconstructed attack sequences rather than treating generative AI output as independently verified incident evidence.

Security Data Preprocessing and Semantic Intelligence Development

The second methodological stage focuses on transforming heterogeneous security records into consistent, contextually meaningful representations. Enterprise security information frequently contains inconsistent timestamp formats, different field names, duplicated events, missing attributes, and variations in event classification. These inconsistencies can negatively influence cross-platform correlation and produce misleading investigation results. Therefore, the preprocessing component performs data validation, timestamp normalization, duplicate detection, schema mapping, missing-value assessment, and event classification. Security records are converted into a common event representation containing attributes such as event time, source address, destination address, user identity, device identifier, cloud resource, activity type, event severity, and associated security indicators. Where information is incomplete, the framework preserves the missing-data status rather than automatically generating unsupported values. Temporal normalization establishes a consistent event sequence across distributed systems, while entity resolution identifies potentially identical users, devices, applications, and infrastructure resources appearing under different identifiers. Following preprocessing, the semantic intelligence component maps normalized events into a structured cybersecurity ontology. The ontology defines relationships among entities such as users, accounts, endpoints, network addresses, cloud workloads, applications, vulnerabilities, attack techniques, and security incidents. Semantic relationships are expressed through meaningful predicates, including authenticated_by, connected_to, accessed, executed_on, associated_with, exploited, and affected. For example, a suspicious authentication event may be associated with an unusual IP address, followed by unauthorized access to a cloud resource and unexpected data transfer. These events are represented as connected security relationships rather than isolated log entries. The methodology additionally integrates standardized threat intelligence concepts to classify observed activities according to recognized adversary tactics and techniques. Security indicators are enriched using approved threat intelligence repositories and historical enterprise incident information. Entity relationships are evaluated according to temporal consistency, source reliability, and supporting evidence. The resulting semantic representation enables the framework to identify potentially coordinated activities across infrastructure boundaries. Importantly, the methodology distinguishes direct observations from inferred relationships so that investigators can understand whether a connection is supported by an original security record or generated through analytical correlation. This distinction improves investigation transparency and reduces the possibility of treating coincidental event relationships as confirmed attack progression.

Knowledge Graph Construction and Generative AI-Based Threat Reconstruction

The third stage develops the knowledge graph and integrates Generative AI for contextual threat reconstruction. The knowledge graph represents security entities as nodes and their observed or inferred relationships as edges. Nodes




Figure 1: System architecture for multi-tier cyber threat reconstruction and semantic narrative generation across distributed enterprise networks.

may include enterprise users, privileged accounts, endpoint devices, IP addresses, cloud workloads, applications, vulnerabilities, malicious indicators, and security incidents. Each node contains relevant metadata, while each relationship includes supporting event identifiers, timestamps, source information, and confidence attributes. Graph construction follows the semantic ontology established during preprocessing, ensuring that different security sources contribute to a consistent representation of enterprise threat activity. Graph traversal and relationship analysis are used to identify suspicious paths connecting initial access, privilege escalation, lateral movement, resource exploitation, and potential data exfiltration. Temporal constraints are applied to prevent unrelated activities from being combined into an artificial attack sequence. Graph analytics also support identification of highly connected entities, suspicious access patterns, repeated communication relationships, and infrastructure components potentially affected by a common threat actor. Generative AI is integrated through a retrieval-augmented investigation pipeline. Rather than supplying unrestricted security data directly to the language model, the framework retrieves relevant graph relationships, original event records, threat intelligence descriptions, and organizational security policies based on the investigation query. The retrieved evidence is assembled into a structured context containing event chronology, affected entities, observed indicators, confidence information, and supporting references. The generative model uses this context to produce a structured threat reconstruction describing the potential attack origin, observed progression, affected resources, suspicious actions, and possible consequences. It also generates investigation summaries, identifies evidence gaps, and recommends additional verification activities. The generation process follows evidence-grounding instructions requiring each significant conclusion to reference supporting records. Where evidence is insufficient, the system must communicate uncertainty instead of presenting speculative findings as established facts. The methodology also considers the use of graph retrieval and vector-based semantic search to improve the identification of relevant historical incidents and technical documentation. Model outputs are subsequently evaluated against the retrieved evidence to identify unsupported statements, inconsistent timelines, and incorrect entity relationships. This stage combines semantic reasoning with generative explanation

to transform complex distributed security information into understandable incident narratives. The knowledge graph remains the primary representation of relationships, while Generative AI serves as an analytical and communication layer that assists investigators in understanding the reconstructed incident.

Experimental Evaluation, Performance Measurement, and Validation

The final methodological stage evaluates the proposed framework through controlled experiments using representative distributed enterprise security scenarios. The experimental environment is designed to simulate hybrid and multi-cloud infrastructure containing virtual machines, containerized applications, enterprise identity services, network gateways, cloud storage resources, and interconnected application services. Simulated attack scenarios may include credential compromise, unauthorized privilege escalation, suspicious API access, lateral movement, malicious workload execution, exploitation of vulnerable services, and unauthorized data transfer. Security events generated during these scenarios are collected from multiple infrastructure sources and processed through the proposed architecture. The experimental evaluation compares the integrated framework with conventional rule-based event correlation and security investigation approaches. Performance is examined using several indicators, including threat reconstruction precision, recall, F1-score, attack-sequence completeness, investigation latency, evidence traceability, and computational resource utilization. Precision measures the proportion of correctly identified reconstructed attack relationships among all identified relationships, while recall measures the proportion of relevant attack relationships successfully recovered. F1-score provides a balanced assessment of precision and recall. Investigation latency measures the time required to transform collected security evidence into an actionable reconstruction. Attack-sequence completeness examines whether the framework identifies the major stages of a predefined attack scenario. Evidence traceability evaluates whether generated findings can be connected to their original security records. Additional evaluation examines the reliability of generative explanations, including factual consistency, source attribution, unsupported inference frequency, and analyst interpretability. Ablation experiments are conducted to assess the individual contributions of semantic intelligence, knowledge graph correlation, and Generative AI. For example, the full framework is compared with configurations that exclude semantic enrichment, graph-based relationships, or retrieval-augmented generation. This analysis helps determine which components contribute most significantly to reconstruction performance. Human security analysts can independently review reconstructed incidents to assess whether generated narratives accurately represent the underlying evidence. The evaluation also considers operational limitations such as incomplete logs, delayed event delivery, inconsistent infrastructure identifiers, adversarially manipulated inputs, and prompt injection attempts. Privacy and governance controls are examined to ensure that sensitive security records are processed according to organizational access policies. The methodology does not assume that generated explanations establish definitive threat attribution; instead, attribution remains subject to independent verification and corroborating evidence. Quantitative results should be calculated from the implemented experimental environment, with repeated trials and appropriate statistical comparisons used to establish reliability. Overall, this evaluation approach provides a systematic basis for determining whether the integration of cloud-driven data collection, semantic intelligence, knowledge graphs, and Generative AI improves enterprise threat reconstruction accuracy, investigation efficiency, and security decision-making across distributed networks.

Results And Discussion

The proposed cloud-driven threat reconstruction framework demonstrates the potential of Generative Artificial Intelligence (GenAI) and semantic intelligence to improve cybersecurity investigation across distributed enterprise networks. By integrating cloud security logs, network traffic records, identity access events, endpoint activities, and application-level monitoring data, the framework provides a unified approach to identifying and reconstructing complex cyberattacks. The generative AI component analyzes heterogeneous security information and correlates related events to identify suspicious activities, while semantic intelligence establishes contextual relationships between users, devices, applications, network resources, and potential attackers. The framework supports the reconstruction of attack sequences by identifying initial access attempts, privilege escalation, lateral movement, data access, and possible exfiltration activities. Compared with conventional rule-based security monitoring, the proposed approach offers improved contextual interpretation and supports the investigation of sophisticated attacks that generate distributed and fragmented evidence. Furthermore, cloud-based processing enables scalable analysis of large volumes of security information across hybrid and multi-cloud environments. These capabilities indicate that combining generative models with semantic reasoning can improve the completeness, consistency, and interpretability of enterprise threat investigations.

The discussion further highlights the importance of semantic intelligence in understanding relationships among cybersecurity events that may appear unrelated when examined independently. Traditional security information and event management systems frequently depend on predefined detection rules, signatures, and threshold-based alerts, which can generate false positives and overlook previously unknown attack patterns. In contrast, the proposed framework uses semantic representations and knowledge-based relationships to connect suspicious activities across different cloud services and enterprise infrastructure components. Generative AI assists investigators by producing contextual summaries, identifying possible attack sequences, and explaining relationships between observed security events. For example, an unusual authentication attempt followed by privilege modification and unauthorized database access can be interpreted as a connected attack scenario rather than three independent alerts. The integration of temporal event correlation, entity relationship analysis, and contextual reasoning provides a more comprehensive understanding of potential security incidents. However, the quality of reconstruction depends on the completeness, accuracy, and synchronization of collected evidence. Incomplete logs, inconsistent timestamps, encrypted traffic, and adversarially manipulated records may affect investigation accuracy. Therefore, evidence validation, confidence scoring, human verification, and secure data governance remain essential components of the proposed architecture.

Another important result concerns the operational advantages of integrating generative AI into cloud-based digital forensics and incident response processes. The framework can reduce the manual effort required to examine large-scale security datasets by automating event summarization, evidence classification, attack timeline generation, and preliminary incident reporting. Security analysts can use its contextual explanations to understand complex attack behavior and prioritize incidents according to their potential impact on enterprise resources. The distributed architecture also supports investigation across geographically separated cloud environments while maintaining centralized visibility into security events. Nevertheless, generative models may produce inaccurate explanations, overlook subtle attack indicators, or infer relationships that are not sufficiently supported by available evidence. Such limitations require retrieval-grounded

generation, source-level evidence references, model confidence assessment, and human approval before critical security decisions are implemented. Overall, the proposed framework establishes a promising foundation for intelligent threat reconstruction by combining generative reasoning, semantic event correlation, and cloud-scale analytics. Its effectiveness should be further established through controlled experiments measuring detection precision, recall, reconstruction completeness, investigation time, processing latency, and computational overhead against conventional security investigation approaches.

Conclusion

The research on Cloud-Driven Threat Reconstruction Using Generative AI and Semantic Intelligence Across Distributed Enterprise Networks presents an intelligent approach to addressing the growing complexity of cybersecurity investigations in modern cloud infrastructures. The proposed framework combines generative artificial intelligence, semantic intelligence, distributed cloud data processing, and contextual event correlation to reconstruct cyberattack activities from heterogeneous security evidence. By integrating information from network monitoring systems, cloud access logs, endpoint protection platforms, identity management services, and enterprise applications, the framework provides a comprehensive representation of security incidents. Generative AI supports automated investigation by interpreting complex security records, summarizing suspicious activities, and generating understandable descriptions of potential attack sequences. Semantic intelligence strengthens this process by identifying relationships among users, devices, services, resources, and attack indicators. This combination helps overcome the limitations of isolated alert analysis and traditional signature-based detection systems. The framework also supports the identification of multi-stage attacks involving unauthorized access, privilege escalation, lateral movement, and sensitive data exposure. Its cloud-driven architecture provides flexibility, scalability, and centralized investigation capabilities across distributed enterprise networks. Consequently, the proposed approach contributes to the development of intelligent cybersecurity investigation systems capable of improving threat visibility, reducing manual analysis requirements, and supporting timely incident response.

Furthermore, the research emphasizes that reliable threat reconstruction requires more than automated event correlation and generative explanations. Evidence integrity, semantic consistency, explainability, privacy protection, and investigation reproducibility must be maintained throughout the forensic process. Generative AI should therefore operate within a controlled architecture that connects every generated conclusion to verified source evidence. The incorporation of knowledge graphs, temporal correlation, confidence evaluation, and human-in-the-loop validation can strengthen the reliability of reconstructed attack scenarios. Although the framework offers significant opportunities for improving cybersecurity operations, challenges involving incomplete evidence, model hallucinations, adversarial manipulation, computational requirements, and cross-cloud interoperability remain important considerations. Enterprise security teams must establish appropriate governance policies to ensure that AI-generated investigation results are reviewed before being used for critical operational or legal decisions. Overall, the proposed framework demonstrates how generative AI and semantic intelligence can complement conventional security monitoring and digital forensic techniques. It provides a conceptual foundation for transforming distributed cybersecurity investigations into more automated, context-aware, explainable, and evidence-driven processes. The integration of these technologies can strengthen enterprise cyber resilience and support more effective identification, reconstruction, and understanding of sophisticated cyber threats.

Future Work

Future research can extend the proposed framework by developing more advanced multimodal generative AI architectures capable of processing diverse cybersecurity evidence simultaneously. Current enterprise security investigations involve structured logs, unstructured incident reports, network traffic metadata, endpoint telemetry, authentication records, application traces, and cloud configuration information. Integrating these heterogeneous sources into a unified multimodal investigation architecture could improve the identification of complex relationships between security events. Future implementations may explore large language models, graph neural networks, transformer-based temporal learning, and retrieval-augmented generation to improve contextual threat analysis. Knowledge graphs can be enhanced with dynamic relationship updates to represent changing enterprise infrastructure, user behavior, resource dependencies, and attacker techniques. Furthermore, temporal reasoning mechanisms could reconstruct attack progression with greater precision by analyzing event ordering, timestamps, behavioral transitions, and dependencies between suspicious activities. Research can also investigate specialized generative models trained on cybersecurity knowledge to improve the interpretation of cloud-native attacks, identity-based threats, malicious API activities, and sophisticated lateral movement. Such models should incorporate evidence-grounded generation, uncertainty estimation, and explainable reasoning to minimize unsupported conclusions. The development of standardized semantic schemas and interoperable evidence representations could further enable consistent investigation across multiple cloud providers and enterprise security platforms. Experimental validation using benchmark datasets, simulated attack environments, and carefully governed enterprise telemetry will be necessary to determine the practical benefits of these developments.

Another important direction for future work involves developing autonomous and collaborative cyber investigation capabilities through multi-agent AI systems. Multiple specialized agents could perform different investigation functions, including evidence collection, anomaly identification, semantic correlation, attack-path reconstruction, forensic validation, and incident report generation. These agents could collaborate through secure communication mechanisms to investigate complex attacks distributed across hybrid and multi-cloud environments. Future systems may also integrate automated response orchestration to recommend containment measures, revoke compromised credentials, isolate affected workloads, and initiate recovery procedures after appropriate human authorization. Reinforcement learning and adaptive behavioral analytics could improve the ability of the framework to recognize evolving attack strategies and changing enterprise activity patterns. Privacy-preserving federated learning may enable organizations to exchange threat intelligence and improve model performance without directly sharing confidential security records. Additional research should investigate adversarial robustness, prompt-injection resistance, model poisoning prevention, evidence provenance, and cryptographic integrity verification to protect the investigation process against manipulation. Performance optimization will also be important for reducing inference latency, processing overhead, and cloud infrastructure costs. Future evaluation should consider detection accuracy, false-positive rates, attack reconstruction completeness, evidence traceability, investigation time, scalability, and operational reliability. Finally, practical deployment studies across financial services, healthcare, manufacturing, government, and large-scale enterprise environments could assess the framework's adaptability to different regulatory and operational requirements. These developments can establish a more trustworthy, scalable,

and intelligent cybersecurity investigation ecosystem in which generative AI and semantic intelligence support proactive threat understanding and resilient enterprise cloud security.

References

Nguyen, G., Dlugolinsky, S., Bobák, M., Tran, V., López García, Á., Heredia, I., Malík, P., & Hluchý, L. (2019). Machine learning and deep learning frameworks and libraries for large-scale data mining: A survey. Artificial Intelligence Review, 52, 77–124. https://doi.org/10.1007/s10462-018-09679-z

Ahuja, D. (2025, August). Edge-AI Enabled Telemetry System for Real-Time Predictive Maintenance in Commercial Computing Frameworks. In 2025 Global Conference on Information Technology and Communication Networks (GITCON) (pp. 1-7). IEEE.

Mudunuri, P. R. (2024). Designing high-availability automation architectures for mission-critical research systems. International Journal of Engineering & Extended Technologies Research, 6(6), 9399–9411. https://doi.org/10.15662/IJEETR.2024.0606038

Aragani, V. M., Maroju, P. K., & Mudunuri, L. N. R. (2024, December). Implementing Non-functional Production Regression Testing with Kubernetes. In International Conference on Information and Communication Technology for Competitive Strategies (pp. 231-244). Singapore: Springer Nature Singapore.

Selvarajan, K. (2023). Designing multi-cloud data platforms for large-scale enterprise workloads. International Journal of Engineering & Extended Technologies Research (IJEETR), 5(1), 5992-6002.

Kavuru, R. R., & Balaji, R. (2023). Extending the service mesh into a compliance enforcement fabric: A policy-aware architecture for regulated financial platforms. International Journal of Engineering & Extended Technologies Research, 5(3), 6638–6644.

Abd-Rouf, M. S. K., Adigun, P. O., Alalade, E. O., Oyekanmi, T. T., Faniyi, A. J., Oladapo, B., Awopejo, T. E., Adegoke, O. S., Jamiu, A., Michael, O. B., Obisesan, A., Ajala, S., Adekanye, M. A., Yambali, P. M., & Abd-Rouf, A. B. (2024). From molecular profiling to predictive algorithms: A conceptual machine-learning framework for mechanism-informed therapy selection in multidrug-resistant cancer. International Journal of Research and Applied Innovations, 7(3), 10892–10909.

Kommineni, R. (2024). Normalize the inputs, not the clouds: Schema-validated profile generation and collision-free address planning for multi-cloud infrastructure as code. International Journal of Emerging Trends in Engineering and Management Research, 9(4), 16116–16123.

Ambati, K. C. (2024). The rise of augmented data analytics how AI is transforming business insights. International Journal of Computer Technology and Electronics Communication, 7(6), 10068–10076.

Tarigoppula, S. (2021). Policy-driven autonomous infrastructure provisioning: A framework for enterprise cloud governance using infrastructure as code. International Journal of Humanities and Information Technology, Special Issue 1, 131–141.

Karrothu, A. (2024). Automated risk-based security controls for vulnerability detection and prevention across cloud-native software development lifecycles. International Journal of Humanities and Information Technology, 6(03), 147–166.

Bellundagi, M. (2025). Digital transformation framework for smart enterprises using AI and cloud computing. The Eastasouth Journal of Information System and Computer Science, 3(2), 366–378. https://doi.org/10.58812/esiscs.v3i02.1299

Natta, P. K. (2022). Predictive detection of lost sales opportunities using inventory signal prioritization in omnichannel retail systems. International Journal of

Computer Technology and Electronics Communication, 5(4), 5483–5495.
Ambalakannu, M. (2024). The emergence of AI-powered data analytics revolutionizing business intelligence. International Journal of Research and Applied Innovations, 7(6), 12157–12165.
Ponugoti, M. (2025). AI-Integrated Microservices: Advancing Decision Intelligence in Compliance-Driven Cloud Architectures. Journal Of Engineering And Computer Sciences, 4(7), 1232-1240.
Namdeo, A. (2025). AI-Driven Audio & Speech Analytics as a Cloud BI Input Layer. International Journal of Research Publications in Engineering, Technology and Management (IJRPETM), 8(6), 13358-13367.
Ramasamy, M. (2024). Telemetry-driven network operations: Architectures for analytics and automated remediation. International Journal of Computer Technology and Electronics Communication, 7(2), 8554-8563.
Reddy, K. V. (2021). UVM methodology for industry-specific applications using AI in hardware verification. International Journal of Engineering & Extended Technologies Research, 3(3), 3094–3107.
Gantikota, S. (2023). Integrating SonarQube and IBM AppScan into Enterprise CI/CD Pipelines: A Vulnerability Mitigation Framework Achieving Over Eighty Percent Risk Reduction. International Journal of Emerging Trends in Computer Science and Information Technology, 4(3), 240-244.
Kopparthi, G. S. (2023). Trustworthy artificial intelligence for high-stakes decision-making: Explainability, human oversight, and system reliability. International Journal of Engineering & Extended Technologies Research, 5(4), 6979–6992.
Yadavalli, V. R. (2023). Cutover intelligence mesh: A dependency-aware architecture for enterprise cloud ERP migration. International Journal of Computer Technology and Electronics Communication, 6(4), 7400–7416.
Valavala, S. K. (2023). Applying zero trust to financial microservices through default deny authorization. International Journal of Engineering & Extended Technologies Research, 5(3), 6627–6637.
Manda, P. (2024). Oracle E-Business Suite modernization: The transition from 12.1. 3 to 12.2. 8. International Journal of Research and Applied Innovations, 7(3), 10838-10842.
Panda, S. S. (2025). Breaking dependency chains: Evaluating Microsoft's Maia 100 as an alternative to NVIDIA GPUs in AI workloads. International Journal of Research and Applied Innovations, 8(1), 11720–11735.
Neela, S. (2022). Toward Intelligent Enterprise Integration: Cloud-Native Middleware Design Patterns and Adaptive Stream Orchestration Architectures for Autonomous Real-Time Decisioning. International Journal of Artificial Intelligence, Data Science, and Machine Learning, 3(2), 154-164.
Vemireddy, S. (2025). Observability and resilience engineering for mission-critical tax processing systems. International Journal of Engineering & Extended Technologies Research, 7(4), 10482–10486.
Indurthy, V. S. K. (2025). Phased Migration Strategies for Modernizing Enterprise Data Warehouses. International Journal of Advanced Research in Computer Science & Technology (IJARCST), 8(3), 12170-12178.
Garg, D. K. (2025). Manufacturing execution systems: A comprehensive guide to selection and implementation. International Journal of Research in Computer Applications and Information Technology, 8(1), 2001–2015. https://doi.org/10.34218/IJRCAIT_08_01_146
Bheemisetty, N. (2025). Transforming static server allocation into an adaptive compute for enhanced throughput and SLA compliance. International Journal of Advanced Research in Computer Science & Technology (IJARCST), 8(3), 12187-12196.
Kalakoti, M. K. R. (2022). Dependency-aware migration and resilience validation

of stateful applications to enterprise cloud. International Journal of Research Publications in Engineering, Technology and Management, 5(2), 6582–6590.

Randhi, K. S. (2024). A scalable integration framework for automated utility revenue leakage detection and remediation. International Journal of Research and Applied Innovations, 7(2), 10536–10555.

Nunnaguppala, L. S. C., Sayyaparaju, K. K., & Padamati, J. R. (2021). Securing The Cloud: Automating Threat Detection with SIEM, Artificial Intelligence & Machine Learning. International Journal For Advanced Research In Science & Technology, 11(3), 385.

Gowda, M. K. S. (2024). Generative AI in banking risk and compliance opportunities and control challenges. International Journal of Engineering & Extended Technologies Research, 6(6), 9421–9431.

Basavala, S. R. (2022). Security assessment framework for microservices-based applications using automated penetration testing. International Journal of Humanities and Information Technology, 4(1–3), 327–341.

Suddala, V. R. A. K. (2024). Machine learning for operational excellence: Real-world applications. International Journal of Research and Applied Innovations, 7(6), 12147–12156.

Shaik, N. (2024). AI-driven scheduling for multi-cloud Kubernetes: Lessons from enterprise deployment. International Journal of Research and Applied Innovations, 7(3), 10880–10891.